

Tabulation of Range Lengths

	Range 1		Range 2		Range 3	
	Feet	Meters	Feet	Meters	Feet	Meters
Casings and Liners						
Total Range Length Inclusive Range Length for 95% Or More Of Carload	16.0 - 25.0	4.88 - 7.62	25.0 - 34.0	7.62 - 10.36	34.0 - 48.0	10.36 - 14.63
Permissible Variation (Max)	6.0	1.83	5.0	1.52	6.0	1.83
Permissible Length (Min)	18.0	5.49	28.0	8.53	36.0	10.97
THREADED AND COUPLED TUBING AND CASING USED AS TUBING						
Total Range Length Inclusive Range Length for 100% Of Carload	20.0 - 24.0	6.10 - 7.32	28.0 - 32.0	8.53 - 9.75	38.0 - 42.0	11.58 - 12.80
Permissible Variation (Max)	2.0	0.61	2.0	0.61	2.0	0.61
INTERGRAL JOINT TUBING						
Total Range Length Inclusive Range Length For 100% Of Carload	20.0 - 26.0	6.10 - 7.92	28.0 - 34.0	8.53 - 10.36	38.0 - 45.0	11.58 - 13.72
Permissible Variation (Max)	2.0	0.61	2.0	0.61	2.0	0.61

